



trivum CW165

trivum speaker for ceiling and wall mounting was developed in order to achieve the highest possible efficiency factor combined with the clearest audio reproduction. Distortions and sound colorations are reduced to an absolute minimum resulting in a clear intelligibility.

The CW series are available in two versions and two sizes: mono (CW130/CW165) and stereo (CW130-S/CW165-S).

They are the perfect complement to the trivum multiroom systems.



150W

Power

The CW165 has a high, short-term peak power capacity of 150 watt.

92dB

Efficiency factor

With its efficiency factor of 92 dB/W the CW165 belongs to the market leaders in this size.

8Ω

Impedance

A high impedance of 8 ohm is very important for flush mount speakers since they are usually connected to long cables.

3
0

Tweeter Level

The CW165 has a tweeter level adjustment in order to adjust the sound to spacial and acoustical prerequisites.

Ear icon

Reproduction quality

The loudspeakers impress with clear reproduction and audibility due to the minimization of distortions and sound intelligibility.

Grill icon

Grills

The included round and square grills can be exchanged anytime without the need to remove or exchange the speakers.

Wrench icon

Installation

Fast and easy installation in 3 steps:

- Cut out mounting hole
- Install cable and speaker
- Install the grill

Function

Speaker for ceiling and wall mounting.

Technical Data

Tweeter diameter	25 mm silk dome
Tweeter mounting	pivoted
Tweeter level switch	yes, 0 dB & -3 dB
Woofer diameter	165 mm
Impedance	8 Ω
Power capacity (peak)	150 W
Sensitivity	92 dB/W
Response -3 dB	58 Hz–21 kHz

Grills

Round grill (diameter)	233 mm
Square grill	232 x 232 mm
Magnetic grill fixing	yes

Dimensions

t1	2 mm
d1	224 mm
Ultra thin bezel	1 mm
Ultra shallow grill	3.5 mm
Installation depth (t2)	96 mm
Mounting diameter (d2)	202 mm
Net weight	1660 g

Frequency response

